

CARBIDE TIPPED FIBERGLASS HOLLOW CORE BITS

ICS WIS

SPECIAL PURPOSE

90° POINT

QUICK RELEASE
7/16" HEX SHANK

GROUND
SHORT FLUTE



Carbide Tipped Fiberglass Hollow Core Bits are designed for drilling through hollow core utility poles made from fiberglass and/or composite materials. They are manufactured with a ground short flute and no clearance to create a rigid solid round body to support the drill on center through initial entry hole and opposite side wall without damaging the entry hole.

| SIZE | FLUTE | OAL | ITEM NO. | PRICE |
|-------|-------|-----|---------------|-------|
| 1/2 | 6 | 12 | CTFGHCB032X12 | 46.76 |
| 1/2 | 6 | 18 | CTFGHCB032X18 | 49.90 |
| 1/2 | 6 | 24 | CTFGHCB032X24 | 53.76 |
| 9/16 | 6 | 12 | CTFGHCB036X12 | 49.62 |
| 9/16 | 6 | 18 | CTFGHCB036X18 | 55.02 |
| 9/16 | 6 | 24 | CTFGHCB036X24 | 59.56 |
| 5/8 | 6 | 12 | CTFGHCB040X12 | 52.46 |
| 5/8 | 6 | 18 | CTFGHCB040X18 | 58.60 |
| 5/8 | 6 | 24 | CTFGHCB040X24 | 61.34 |
| 11/16 | 6 | 12 | CTFGHCB044X12 | 54.94 |
| 11/16 | 6 | 18 | CTFGHCB044X18 | 60.90 |
| 11/16 | 6 | 24 | CTFGHCB044X24 | 70.26 |
| 3/4 | 6 | 12 | CTFGHCB048X12 | 58.84 |
| 3/4 | 6 | 18 | CTFGHCB048X18 | 63.90 |
| 3/4 | 6 | 24 | CTFGHCB048X24 | 74.22 |
| 13/16 | 6 | 12 | CTFGHCB052X12 | 62.12 |
| 13/16 | 6 | 18 | CTFGHCB052X18 | 69.10 |

| SIZE | FLUTE | OAL | ITEM NO. | PRICE |
|--------|-------|-----|---------------|--------|
| 13/16 | 6 | 24 | CTFGHCB052X24 | 76.78 |
| 7/8 | 6 | 12 | CTFGHCB056X12 | 71.66 |
| 7/8 | 6 | 18 | CTFGHCB056X18 | 78.88 |
| 7/8 | 6 | 24 | CTFGHCB056X24 | 94.40 |
| 15/16 | 6 | 12 | CTFGHCB060X12 | 81.34 |
| 15/16 | 6 | 18 | CTFGHCB060X18 | 86.84 |
| 15/16 | 6 | 24 | CTFGHCB060X24 | 89.34 |
| 1 | 6 | 12 | CTFGHCB100X12 | 84.40 |
| 1 | 6 | 18 | CTFGHCB100X18 | 91.84 |
| 1 | 6 | 24 | CTFGHCB100X24 | 102.40 |
| 1-1/16 | 6 | 12 | CTFGHCB104X12 | 89.34 |
| 1-1/16 | 6 | 18 | CTFGHCB104X18 | 95.94 |
| 1-1/16 | 6 | 24 | CTFGHCB104X24 | 102.40 |
| 1-1/8 | 6 | 12 | CTFGHCB108X12 | 94.72 |
| 1-1/8 | 6 | 18 | CTFGHCB108X18 | 102.40 |
| 1-1/8 | 6 | 24 | CTFGHCB108X24 | 108.74 |

CARBIDE TIPPED FIBERGLASS SOLID CORE BITS

ICS WIS

SPECIAL PURPOSE

90° POINT

QUICK RELEASE
7/16" HEX SHANK

GROUND
SHORT FLUTE

Carbide Tipped Fiberglass Solid Core Bits are designed for drilling solid/foam core utility poles and cross arms made from fiberglass, resin and composite materials. They are manufactured with full flute and solid body to be able to drill through fiberglass/resin/composite poles. The full fluting allows bit to remove debris from the hole without melting it.

| SIZE | FLUTE | OAL | ITEM NO. | PRICE |
|-------|-------|-----|---------------|-------|
| 1/2 | 9 | 12 | CTFGSCB032X12 | 57.02 |
| 1/2 | 15 | 18 | CTFGSCB032X18 | 59.70 |
| 1/2 | 21 | 24 | CTFGSCB032X24 | 64.04 |
| 9/16 | 9 | 12 | CTFGSCB036X12 | 58.42 |
| 9/16 | 15 | 18 | CTFGSCB036X18 | 64.34 |
| 9/16 | 21 | 24 | CTFGSCB036X24 | 73.12 |
| 5/8 | 9 | 12 | CTFGSCB040X12 | 60.92 |
| 5/8 | 15 | 18 | CTFGSCB040X18 | 73.06 |
| 5/8 | 21 | 24 | CTFGSCB040X24 | 76.78 |
| 11/16 | 9 | 12 | CTFGSCB044X12 | 64.34 |
| 11/16 | 15 | 18 | CTFGSCB044X18 | 73.00 |
| 11/16 | 21 | 24 | CTFGSCB044X24 | 80.38 |
| 3/4 | 9 | 12 | CTFGSCB048X12 | 67.02 |
| 3/4 | 15 | 18 | CTFGSCB048X18 | 73.12 |
| 3/4 | 21 | 24 | CTFGSCB048X24 | 82.88 |
| 13/16 | 9 | 12 | CTFGSCB052X12 | 71.84 |
| 13/16 | 15 | 18 | CTFGSCB052X18 | 79.22 |

| SIZE | FLUTE | OAL | ITEM NO. | PRICE |
|--------|-------|-----|---------------|--------|
| 13/16 | 21 | 24 | CTFGSCB052X24 | 85.32 |
| 7/8 | 9 | 12 | CTFGSCB056X12 | 85.08 |
| 7/8 | 15 | 18 | CTFGSCB056X18 | 90.14 |
| 7/8 | 21 | 24 | CTFGSCB056X24 | 99.96 |
| 15/16 | 9 | 12 | CTFGSCB060X12 | 87.22 |
| 15/16 | 15 | 18 | CTFGSCB060X18 | 94.96 |
| 15/16 | 21 | 24 | CTFGSCB060X24 | 102.28 |
| 1 | 9 | 12 | CTFGSCB100X12 | 89.66 |
| 1 | 15 | 18 | CTFGSCB100X18 | 97.46 |
| 1 | 21 | 24 | CTFGSCB100X24 | 109.72 |
| 1-1/16 | 9 | 12 | CTFGSCB104X12 | 97.46 |
| 1-1/16 | 15 | 18 | CTFGSCB104X18 | 103.08 |
| 1-1/16 | 21 | 24 | CTFGSCB104X24 | 115.82 |
| 1-1/8 | 9 | 12 | CTFGSCB108X12 | 99.78 |
| 1-1/8 | 15 | 18 | CTFGSCB108X18 | 104.84 |
| 1-1/8 | 21 | 24 | CTFGSCB108X24 | 118.20 |