

# HIGH SPEED STEEL CHUCKING REAMERS - STRAIGHT SHANK

**ICS**    **WIS**

**GENERAL PURPOSE**

**RIGHT HAND CUT**



STRAIGHT FLUTE



HELICAL FLUTE

High Speed Steel Straight Shank Straight Flute Chucking Reamers are designed for general purpose reaming of most ferrous and non-ferrous metals. The cutting edge is ground with a 45° chamfer angle for easy hole entry. They are also known as Machine Reamers.

High Speed Steel Helical Flute Chucking Reamers are designed for reaming materials where additional shear is necessary and to improve chip removal in blind holes. The cutting edge is ground with a 45° chamfer angle for easy hole entry. They are also known as Machine Reamers.

## Fractional Sizes (Straight Shank) 3/64" To 2" Dia.

SIZE	DEC. EQUIV.	SHANK DIA.	FLUTE LENGTH	OVERALL LENGTH	HSS	
					STRAIGHT FLUTE	HELICAL FLUTE
					CRSF	CRHF
3/64	.0469	.0455	1/2	2-1/2	\$13.34	\$ -
1/16	.0629	.0585	1/2	2-1/2	13.34	-
5/64	.0781	.0720	3/4	3	11.76	-
3/32	.0938	.0880	3/4	3	10.08	-
7/64	.1094	.1030	7/8	3-1/2	11.76	-
1/8	.1250	.1190	7/8	3-1/2	8.86	11.48
9/64	.1406	.1350	1	4	14.12	16.16
5/32	.1562	.1510	1	4	13.10	16.16
11/64	.1719	.1645	1-1/8	4-1/2	14.12	16.16
3/16	.1875	.1805	1-1/8	4-1/2	13.10	16.16
13/64	.2031	.1945	1-1/4	5	17.30	18.26
7/32	.2188	.2075	1-1/4	5	16.54	17.86
15/64	.2344	.2265	1-1/2	6	17.30	18.26
1/4	.2500	.2405	1-1/2	6	14.24	16.70
17/64	.2656	.2485	1-1/2	6	19.02	20.32
9/32	.2812	.2485	1-1/2	6	19.02	20.32
19/64	.2969	.2807	1-1/2	6	20.44	20.32
5/16	.3125	.2807	1-1/2	6	16.80	18.94
21/64	.3281	.2807	1-1/2	6	21.84	22.80
11/32	.3438	.2807	1-1/2	6	21.84	22.80
23/64	.3594	.3120	1-3/4	7	21.84	22.80
3/8	.3750	.3120	1-3/4	7	18.48	22.08
25/64	.3906	.3120	1-3/4	7	22.30	25.38
13/32	.4062	.3120	1-3/4	7	22.30	25.38
27/64	.4219	.3745	1-3/4	7	25.06	26.56
7/16	.4375	.3745	1-3/4	7	22.30	25.38
29/64	.4531	.3745	1-3/4	7	27.90	27.40
15/32	.4688	.3745	1-3/4	7	26.62	27.30
31/64	.4844	.4375	2	8	27.90	28.52
1/2	.5000	.4375	2	8	23.46	25.54
33/64	.5156	.4375	2	8	41.18	43.12
17/32	.5313	.4375	2	8	29.80	33.04
35/64	.5469	.4375	2	8	40.28	43.12
9/16	.5625	.4375	2	8	28.56	31.92
37/64	.5781	.4375	2	8	46.60	48.40
19/32	.5938	.4375	2	8	34.06	37.06
39/64	.6094	.5620	2-1/4	9	46.60	48.06
5/8	.6250	.5620	2-1/4	9	32.48	34.96
41/64	.6406	.5620	2-1/4	9	53.44	55.12

SIZE	DEC. EQUIV.	SHANK DIA.	FLUTE LENGTH	OVERALL LENGTH	HSS	
					STRAIGHT FLUTE	HELICAL FLUTE
					CRSF	CRHF
21/32	.6562	.5620	2-1/4	9	\$39.04	\$41.62
43/64	.6719	.5620	2-1/4	9	61.16	41.62
11/16	.6875	.5620	2-1/4	9	37.86	40.88
45/64	.7031	.5620	2-1/4	9	61.16	40.88
23/32	.7188	.5620	2-1/4	9	44.14	47.22
47/64	.7344	.6245	2-1/2	9-1/2	47.82	47.22
3/4	.7500	.6245	2-1/2	9-1/2	40.32	46.26
49/64	.7656	.6245	2-1/2	9-1/2	66.08	46.26
25/32	.7812	.6245	2-1/2	9-1/2	50.18	53.10
51/64	.7969	.6245	2-1/2	9-1/2	66.08	53.10
13/16	.8125	.6245	2-1/2	9-1/2	49.24	53.10
53/64	.8281	.6245	2-1/2	9-1/2	76.16	53.10
27/32	.8438	.6245	2-1/2	9-1/2	56.96	59.64
55/64	.8594	.7495	2-5/8	10	76.16	59.94
7/8	.8750	.7495	2-5/8	10	54.56	59.66
57/64	.8906	.7495	2-5/8	10	84.00	59.66
29/32	.9062	.7495	2-5/8	10	62.84	66.08
59/64	.9219	.7495	2-5/8	10	84.00	66.08
15/16	.9375	.7495	2-5/8	10	61.58	66.08
61/64	.9531	.7495	2-5/8	10	93.92	66.08
31/32	.9688	.7495	2-5/8	10	70.54	74.48
63/64	.9844	.8745	2-3/4	10-1/2	93.92	74.48
1	1.0000	.8745	2-3/4	10-1/2	67.10	74.48
1- 1/32	1.0312	.8745	2-3/4	10-1/2	83.28	74.48
1- 1/16	1.0625	.8745	2-3/4	10-1/2	77.84	83.78
1- 3/32	1.0938	.8745	2-7/8	11	94.96	83.78
1- 1/8	1.1250	.8745	2-7/8	11	83.28	92.26
1- 5/32	1.1562	.8745	2-7/8	11	103.18	92.26
1- 3/16	1.1875	.9995	2-7/8	11	94.96	101.54
1- 1/4	1.2500	.9995	3	11-1/2	103.18	112.68
1- 5/16	1.3125	.9995	3	11-1/2	123.76	123.54
1- 3/8	1.3750	.9995	3-1/4	12	123.76	135.50
1- 7/16	1.4375	1.2495	3-1/2	12-1/2	149.52	146.70
1- 1/2	1.5000	1.2495	3-1/2	12-1/2	144.48	156.80
1- 9/16	1.5625	1.2495	3-1/2	12-1/2	201.60	-
1- 5/8	1.6250	1.2495	3-1/2	13	224.46	-
1-11/16	1.6875	1.2495	3-1/2	13	245.70	-
1- 3/4	1.7500	1.2495	4	13-1/2	258.32	-
1- 7/8	1.8750	1.5000	4	14	297.04	-
2	2.0000	1.5000	4	14	315.84	-

TOLERANCES
3/64 - 1/2 dia.: +.0002 -.0000"
33/64 - 5/8 dia.: +.0003 -.0000"
41/64 - 1-1/2 dia.: +.0001 -.0005"
1-9/16 - 2 dia.: +.0002 -.0006"

NUMBER OF FLUTES	
3/64 - 5/32 dia.: 4 Flutes	1-3/8 - 1-1/2 dia.: 12 Flutes
11/64 - 39/64 dia.: 6 Flutes	1-9/16 - 1-7/8 dia.: 14 Flutes
5/8 - 1-1/32 dia.: 8 Flutes	2" dia.: 16 Flutes
1-1/16 - 1-5/16 dia.: 10 Flutes	