


HIGH SPEED STEEL TOWER BOLT REAMERS

ICS **WIS**

SPECIAL PURPOSE

RIGHT HAND CUT

STRAIGHT SHANK



LEFT HAND FLUTE

HELICAL FLUTE

Tower bolt reamers are designed for lining up bolt holes on cell phone towers, wind mills, and transmission towers. They have three flats on the shank for use in 1/2" three jaw power tools and pneumatic equipment. The extra short length makes them more useful in close quarters.

ITEM NO.	SIZE	SHANK DIAMETER	DIAMETER AT POINT	FLUTE LENGTH	OVERALL LENGTH	PRICE EACH
TBR036	9/16	1/2	13/64	1-39/64	3-1/2	\$44.88
TBR044	11/16	1/2	3/8	2-3/64	3-21/64	58.46
TBR052	13/16	1/2	15/32	2-59/64	4-51/64	78.26

TOWER BOLT REAMER SET

DESCRIPTION	ITEM NO.	TOWER BOLT REAMER SIZES	PRICE
<p>3 PIECE - HIGH SPEED STEEL</p>	TBRS-3	9/16, 11/16, 13/16	\$181.90

HIGH SPEED STEEL PIPE REAMERS

ICS **WIS**


SPECIAL PURPOSE

RIGHT HAND CUT

Taper Pipe Reamers are manufactured with a taper of 3/4" per foot. They are used prior to tapping dry seal and ANPT threads when high quality threads are required.



STRAIGHT FLUTE



SPIRAL FLUTE

Straight Flute Pipe Reamers are designed for use in easy to ream materials.

Spiral Flute Pipe Reamers are designed for reaming harder materials where additional shear is needed.

SIZE	SHANK DIA.	DIAMETER		FLUTE LENGTH	OVERALL LENGTH	NO. OF FLUTES	HIGH SPEED STEEL	
		SMALL END	LARGE END				STRAIGHT FLUTE PRSF	SPIRAL FLUTE PRSF
1/16	.3125	.2320	.2910	3/4	2	6	\$18.60	\$22.44
1/8	.4375	.3160	.3620	3/4	2-1/8	6	18.60	22.44
1/4	.5625	.4060	.4620	1-1/16	2-7/16	6	30.68	27.36
3/8	.7000	.5400	.6060	1-1/16	2-9/16	8	38.88	30.00
1/2	.6875	.6650	.7510	1-3/8	3-1/8	8	43.24	47.50
3/4	.9063	.8760	.9620	1-3/8	3-1/4	10	57.20	67.60
1	1.1250	1.1030	1.2120	1-3/4	3-3/4	10	88.80	96.72
1-1/4	1.3125	1.4440	1.5530	1-3/4	4	10	132.16	157.36
1-1/2	1.5000	1.6840	1.7930	1-3/4	4-1/4	10	195.08	191.60
2	1.8750	2.1590	2.2680	1-3/4	4-1/2	12	270.40	254.16
2-1/2	2.2050	2.5610	2.7720	2-5/8	5-1/2	12	485.60	540.00
3	2.6250	3.2020	3.3800	2-3/4	6	12	636.80	708.00