

HIGH SPEED STEEL TAPER SHANK BRIDGE REAMERS

ICS

WIS

HEAVY DUTY

RIGHT HAND CUT

LONG BODY




LEFT HAND FLUTE

STRAIGHT FLUTE

HELICAL FLUTE

High Speed Steel Taper Shank Bridge Reamers are designed for use in structural steel fabrication bridge work and ship construction to line up bolt and rivet holes. The front portion of the reamer is tapered at approximately 1" in 10 and the balance of the flute is parallel. They can be used in portable electric or pneumatic equipment. NOTE: Because of the heavy duty work involved, some sizes have larger Morse Taper shanks than is usual for the diameter. These tools are also referred to as Boilermaker's Reamers, Rivet Hole Reamers, Aligning Reamers, or Construction Taper Reamers.

SIZE	DEC. EQUIV.	DIA. AT POINT	FLUTE LENGTH	OVERALL LENGTH	TAPER SHANK	MORSE		HSS		SIZE	DEC. EQUIV.	DIA. AT POINT	FLUTE LENGTH	OVERALL LENGTH	TAPER SHANK	MORSE		HSS	
						STRAIGHT FLUTE BRSF	HELICAL FLUTE BRHF	STRAIGHT FLUTE BRSF	HELICAL FLUTE BRHF							STRAIGHT FLUTE BRSF	HELICAL FLUTE BRHF		
5/16	.3125	11/64	4-3/8	8-1/4	2			\$33.20	\$33.20	1-1/8	1.1250	55/64	7-3/8	12	3	\$104.72	\$104.72		
3/8	.3750	7/32	4-3/8	8-1/4	2			33.20	33.20	1-3/16	1.1875	59/64	7-3/8	12	3	116.44	116.44		
13/32	.4062	7/32	5-1/8	8-1/4	2			33.20	33.20	1-1/4	1.2500	63/64	7-3/8	13	4	129.48	129.48		
7/16	.4375	17/64	4-3/8	8-1/4	2			37.26	37.26	1-5/16	1.3125	1-1/16	7-3/8	13	4	141.08	141.08		
15/32	.4688	9/32	5-1/8	8-1/4	2			37.52	37.52	1-3/8	1.3750	1-1/8	7-3/8	13	4	146.66	146.66		
1/2	.5000	5/16	5-1/8	9	2			37.26	37.26	1-7/16	1.4375	1-3/16	7-3/8	13	4	157.92	157.92		
17/32	.5312	11/32	5-1/8	9	2			39.18	39.18	1-1/2	1.5000	1-1/4	7-3/8	13	4	178.42	178.42		
9/16	.5625	3/8	5-1/8	9	2			39.66	39.66	1-9/16	1.5625	1-1/4	7-3/8	13	4	256.42	256.42		
5/8	.6250	25/64	6-1/8	10	2			48.06	48.06	1-5/8	1.6250	1-1/4	7-3/8	13	4	256.42	256.42		
11/16	.6875	13/32	7-1/8	11-3/4	3			57.74	57.74	1-11/16	1.6875	1-3/8	7-3/8	13	4	273.50	273.50		
3/4	.7500	15/32	7-3/8	12	3			62.02	62.02	1-3/4	1.7500	1-3/8	7-3/8	13	4	307.70	307.70		
13/16	.8125	35/64	7-3/8	12	3			67.36	67.36	1-13/16	1.8125	1-7/16	7-3/8	13	4	324.78	324.78		
7/8	.8750	39/64	7-3/8	12	3			74.76	74.76	1-7/8	1.8750	1-1/2	7-3/8	13	4	341.88	341.88		
15/16	.9375	43/64	7-3/8	12	3			77.03	77.03	1-15/16	1.9375	1-1/2	7-3/8	13	4	359.00	359.00		
1	1.0000	47/64	7-3/8	12	3			85.42	85.42	2	2.0000	1-3/4	7-3/8	13	4	376.10	376.10		
1-1/16	1.0625	13/16	7-3/8	12	3			94.04	94.04	2-1/16	2.0625	1-13/16	7-3/8	13	4	-	430.50		

Larger sizes are available. Inquire for quote.

HIGH SPEED STEEL ROUND SHANK BRIDGE REAMERS

ICS

WIS

HEAVY DUTY

RIGHT HAND CUT

STRAIGHT SHANK



LEFT HAND FLUTE

HELICAL FLUTE

High Speed Steel Round Shank Bridge Reamers are designed for lining up holes in structural steel fabrication bridgework, ship construction, automotive maintenance, and railroad car manufacture. The front portion of the reamer is tapered at approximately 1" in 10 and the balance of the flute is parallel. Can be used with any 1/2" 3 jaw power tool. Round Shank design helps prevent "whip" caused by tool snagging or binding.

SIZE	SHANK DIA.	DIA. AT POINT	FLUTE LENGTH	SHANK LENGTH	HSS	
					STRAIGHT SHANK BRHFRS	BRHFRS
7/16	1/2	17/64	4-3/8	1-1/2		\$42.98
1/2	1/2	5/16	5-1/8	1-1/2		47.36
9/16	1/2	3/8	5-1/8	1-1/2		49.46
5/8	1/2	25/64	6-1/8	1-1/2		55.92
11/16	1/2	13/32	7-1/8	1-1/2		65.78
3/4	1/2	15/32	7-3/8	1-1/2		70.14
13/16	1/2	35/64	7-3/8	1-1/2		70.14
7/8	1/2	39/64	7-3/8	1-1/2		76.70
15/16	1/2	43/64	7-3/8	1-1/2		78.84

SIZE	SHANK DIA.	DIA. AT POINT	FLUTE LENGTH	SHANK LENGTH	HSS	
					STRAIGHT SHANK BRHFRS	BRHFRS
1	1/2	47/64	7-3/8	1-1/2		\$86.76
1-1/16	1/2	13/16	7-3/8	1-1/2		94.88
1-1/8	*1/2	55/64	7-3/8	1-1/2		104.88
1-3/16	*1/2	59/64	7-3/8	1-1/2		115.88
1-1/4	*1/2	63/64	7-3/8	1-1/2		128.34
1-5/16	*1/2	1-1/16	7-3/8	1-1/2		145.50
1-3/8	*1/2	1-1/8	7-3/8	1-1/2		156.50
1-7/16	*1/2	1-3/16	7-3/8	1-1/2		167.52
1-1/2	*1/2	1-1/4	7-3/8	1-1/2		187.58

* Optional 3/4" Dia. Shank

Note: If work space is limited, consider using car reamers or tower bolt reamers to do the same job.