

HIGH SPEED STEEL HEXAGON THREADING DIES


ICS USA

HEAVY DUTY

GROUND THREAD

HSS Hex Threading Dies are designed for tough cutting applications of all types of external threads. They are used for threading rods, bolts, and studs. Two standard diameters of Hex Dies simplify die stock handle requirements. ICS Hex Threading Dies have polished gold face and black surface treated threads for maximum performance.

STANDARD DIA.
ACROSS FLATS



RIGHT HAND
CUT

BLACK & GOLD FINISH

Machine Screw and Fractional Sizes (#4 To 3/4" Dia.)

| THREADS | | DIAMETER | | ITEM | |
|---------|----------|--------------|------------|-------|--|
| SIZE | PER INCH | ACROSS FLATS | NO. | PRICE | |
| 4 | 40 | 1 | HXTD#04-40 | 10.58 | |
| 6 | 32 | 1 | HXTD#06-32 | 10.58 | |
| 8 | 32 | 1 | HXTD#08-32 | 10.58 | |
| 10 | 24 | 1 | HXTD#10-24 | 10.58 | |
| 10 | 32 | 1 | HXTD#10-32 | 10.58 | |
| 12 | 24 | 1 | HXTD#12-24 | 10.58 | |
| 1/4 | 20 | 1 | HXTD016-20 | 10.58 | |
| 1/4 | 28 | 1 | HXTD016-28 | 10.58 | |
| 5/16 | 18 | 1 | HXTD020-18 | 10.58 | |
| 5/16 | 24 | 1 | HXTD020-24 | 10.58 | |
| 3/8 | 16 | 1 | HXTD024-16 | 10.58 | |
| 3/8 | 24 | 1 | HXTD024-24 | 10.58 | |

| THREADS | | DIAMETER | | ITEM | |
|---------|----------|--------------|-------------|-------|--|
| SIZE | PER INCH | ACROSS FLATS | NO. | PRICE | |
| 7/16 | 14 | 1 | HXTD028-14 | 10.58 | |
| 7/16 | 20 | 1 | HXTD028-20 | 10.58 | |
| 1/2 | 13 | 1 | HXTD032-13 | 10.58 | |
| 1/2 | 20 | 1 | HXTD032-20 | 10.58 | |
| 1/2 | 13 | 1-7/16 | HXTD032-13A | 23.66 | |
| 1/2 | 20 | 1-7/16 | HXTD032-20A | 23.66 | |
| 9/16 | 12 | 1-7/16 | HXTD036-12 | 23.66 | |
| 9/16 | 18 | 1-7/16 | HXTD036-18 | 23.66 | |
| 5/8 | 11 | 1-7/16 | HXTD040-11 | 23.66 | |
| 5/8 | 18 | 1-7/16 | HXTD040-18 | 23.66 | |
| 3/4 | 10 | 1-7/16 | HXTD048-10 | 23.66 | |
| 3/4 | 16 | 1-7/16 | HXTD048-16 | 23.66 | |

HIGH SPEED STEEL HEXAGON THREADING (NPT) PIPE DIES


ICS USA

HEAVY DUTY

GROUND THREAD

HSS Hexagon (Hex Nut Dia.) NPT Threading Pipe Dies are designed for external threading or rethreading of taper pipe threads. They are used where a threaded connection will not be required to withstand high fluid or gas pressures and the use of a sealer is acceptable.

STANDARD DIA.
ACROSS FLATS



RIGHT HAND
CUT

BLACK & GOLD FINISH

| THREADS | | DIAMETER | | ITEM | |
|---------|----------|--------------|-------------|-------|--|
| SIZE | PER INCH | ACROSS FLATS | NO. | PRICE | |
| 1/8 | 27 | 1 | HXTDP008-27 | 10.58 | |

| THREADS | | DIAMETER | | ITEM | |
|---------|----------|--------------|--------------|-------|--|
| SIZE | PER INCH | ACROSS FLATS | NO. | PRICE | |
| 1/4 | 18 | 1-7/16 | HXTDP016-18A | 23.66 | |