

## HIGH SPEED STEEL T-SLOT CUTTERS

**ICS USA**

**SPECIAL PURPOSE**

**STAGGERED TEETH**

**WELDON SHANK**



**RIGHT HAND CUT  
RIGHT/LEFT HAND HELIX**

High Speed Steel T-Slot Cutters are designed for milling T-slots into tables and beds of machine tools and similar applications where a good surface finish is required. A vertical slot must be cut first so that neck and shank may enter the cut. Use with standard end mill arbors.

ITEM NO.	BOLT SIZE	CUTTER DIA.	CUTTER THICKNESS	NECK DIA.	SHANK DIA.	OVERALL LENGTH	PRICE EACH
TSC 016	1/4	9/16	15/64	17/64	1/2	2-19/32	\$40.78
TSC 020	5/16	21/32	17/64	21/64	1/2	2-11/16	44.36
TSC 024	3/8	25/32	21/64	13/32	3/4	3-1/4	63.02
TSC 032	1/2	31/32	25/64	17/32	3/4	3-7/16	70.96
TSC 040	5/8	1-1/4	31/64	21/32	1	3-15/16	96.62
TSC 048	3/4	1-15/32	5/8	25/32	1	4-7/16	108.82
TSC 100	1	1-27/32	53/64	1-1/32	1-1/4	4-13/16	182.18
TSC 116	1-1/4	2-7/32	1-3/32	1-9/32	1-1/4	5-3/8	230.00
TSC 132	1-1/2	2-21/32	1-11/32	1-17/32	1-1/4	5-29/32	303.14

## COBALT T-SLOT CUTTERS

**ICS USA**

**SPECIAL PURPOSE**

**STAGGERED TEETH**

**WELDON SHANK**



**RIGHT HAND CUT  
RIGHT/LEFT HAND HELIX**

Cobalt T-Slot Cutters are designed for milling T-slots into tougher materials where a good surface finish is required. They are used for machining hard, high strength materials up to a hardness of 40RC. A vertical slot must be cut first so that neck and shank may enter cut. Use with standard end mill arbors.

ITEM NO.	BOLT SIZE	CUTTER DIA.	CUTTER THICKNESS	NECK DIA.	SHANK DIA.	OVERALL LENGTH	PRICE EACH
TSCC 016	1/4	9/16	15/64	17/64	1/2	2-19/32	\$57.06
TSCC 020	5/16	21/32	17/64	21/64	1/2	2-11/16	61.68
TSCC 024	3/8	25/32	21/64	13/32	3/4	3-1/4	87.66
TSCC 032	1/2	31/32	25/64	17/32	3/4	3-7/16	99.02
TSCC 040	5/8	1-1/4	31/64	21/32	1	3-15/16	134.86
TSCC 048	3/4	1-15/32	5/8	25/32	1	4-7/16	151.60
TSCC 100	1	1-27/32	53/64	1-1/32	1-1/4	4-13/16	255.36
TSCC 116	1-1/4	2-7/32	1-3/32	1-9/32	1-1/4	5-3/8	321.06
TSCC 132	1-1/2	2-21/32	1-11/32	1-17/32	1-1/4	5-29/32	421.12

## COBALT ROUGHING T-SLOT CUTTERS

**ICS USA**

**SPECIAL PURPOSE**

**HELICAL TEETH**

**WELDON SHANK**



**RIGHT HAND CUT**

Cobalt Roughing T-Slot Cutters are designed for rapid milling T-slots into tougher materials where finish is not as important. They are used for most metals, even hardened steel and aerospace alloys. A vertical slot must be cut first so that neck and shank may enter cut. Use with standard end mill arbors.

ITEM NO.	BOLT SIZE	CUTTER DIA.	CUTTER THICKNESS	NECK DIA.	SHANK DIA.	OVERALL LENGTH	PRICE EACH
RTSC 032	1/2	31/32	25/64	17/32	3/4	3-7/16	
RTSC 040	5/8	1-1/4	31/64	21/32	1	3-15/16	
RTSC 048	3/4	1-15/32	5/8	25/32	1	4-7/16	CALL
RTSC 100	1	1-27/32	53/64	1-1/32	1-1/4	4-13/16	
RTSC 116	1-1/4	2-7/32	1-3/32	1-9/32	1-1/4	5-3/8	
RTSC 132	1-1/2	2-21/32	1-11/32	1-17/32	1-1/4	5-29/32	