

GUIDE TO SCREWTHREAD SIZES - page 1

	BRITISH							AMERICAN							ISO INCH & UNIFIED					SI METRIC			ISO METRIC		PIPE SIZE (Bore dia.) Nominal Diameter	PIPE THREADS									
	BSW	BSF	ADMF	BSC	CEI	BS Conduit	Brass	BA	BS Conduit	BA	Pitch mm	Threads per inch	UNC	UNF	12UN	USS	ASME Special	ASME Standard	SAE Regular	SAE Extra Fine	UNC	UNEF	16UN	20UN		28UN	32UN	M.M.A. SI	MB	MC	MISO	MISO	Pg	Armour Pipe	TPI
Major diameter of Thread in mm	Threads per inch							BA No	Pitch mm	Threads per inch							Threads per inch					Pitch in mm			Pitch in mm		in	TPI	Pg No	TPI					
	BSW form for cycles (Italics)							14	.23	In the constant pitch series some sizes are the same as in the graded pitch series							.25	.25 2	 2		.25	.2				For Taper Threads the size given under "Major dia. of Thread" is the Major dia. at the gauging point.	Taper and Parallel (Parallel) Taper and Straight (Parallel) (For threads for High Pressure Copper Tubes see BSP Taper)			DIN 40430			
No 0	.0394	1.0						13	.25																										
	.0433	1.1						12	.28																										
	.0472	1.2																																	
	.0512	1.3																																	
	.0551	1.4																																	
	.056	1.424																																	
	.0591	1.5																																	
	.06	1.524																																	
	.063	1.6																																	
	.064	1.626																																	
	.0669	1.7																																	
	.0709	1.8																																	
	.072	1.829																																	
No 1	.073	1.854																																	
	.0748	1.9																																	
	.0787	2.0																																	
	.08	2.032																																	
	.0825	2.096																																	
No 2	.086	2.184																																	
	.0866	2.2																																	
	.0905	2.299																																	
	.0906	2.3																																	
	.092	2.337																																	
$\frac{3}{32}$.0938	2.387																																	
	.0984	2.5																																	
No 3	.099	2.515																																	
	.1024	2.6																																	
	.1025	2.604																																	
	.104	2.642																																	
	.1102	2.8																																	
No 4	.112	2.845																																	
	.1145	2.908																																	
	.1181	3.0																																	
$\frac{1}{8}$.125	3.175																																	
	.126	3.2																																	
	.1291	3.279																																	
	.1378	3.5																																	
No 6	.138	3.505																																	
	.1417	3.6																																	
	.1423	3.614																																	
No 7	.151	3.835																																	
	.154	3.911																																	
$\frac{5}{32}$.1562	3.969																																	
	.1575	4.0																																	
	.1583	4.021																																	
	.1614	4.1																																	
No 8	.164	4.166																																	
	.175	4.445																																	
No 9	.177	4.496																																	
	.1772	4.5																																	
	.1776	4.511																																	
	.185	4.7																																	
$\frac{3}{16}$.1875	4.762																																	

GUIDE TO SCREWTHREAD SIZES - page 3

			BRITISH				AMERICAN							ISO INCH & UNIFIED								SI METRIC					ISO METRIC				PIPE THREADS														
Major dia. of Thread in	Major dia. of Thread mm	Major dia. of Thread mm	Threads per inch				Threads per inch							Threads per inch								Pitch in mm					Pitch in mm				in	TPI	Pg	TPI											
			BSW	BSF	ADMF	BSC	CEI	Brass	BS Conduit	ANC	ANF	ANEF	8AN	12AN	16AN	USS	SAE	SAE Regular	SAE Extra Fine	UNC	UNF	UNEF	4UN	6UN	8UN	12UN	16UN	20UN	28UN	32UN	M MA	MB	MC	MD	ME	MISO Coarse	MISO Fine	PIPE SIZE (Bore dia.) Nominal Diameter	BSP & ISO PIPE	NPT NPS (American)	BS Copper Pipe	Pg Armour Pipe			
11/16	.6714 .6875 .7087 .7323 .75	17.054 17.462 18.0 18.6 19.05	11*	14	20	26	26		24		12		11	16	24		24		12	16	20	28	32		2.5	1.5	1.0		2.5	2.0	1.5	1.0	11/16	18		11	18								
3/4	.764 .7874 .8032 .8125 .825 .8356 .8661 .875	19.406 20.0 20.4 20.638 20.955 21.222 22.0 22.225	10*	12	14	26	26	16	10	16	20	12	16	10	16	20	10	16	20					12	16	20	28	32		2.5	1.5	1.0		2.5	2.0	1.5	1.0	11/16	20		13.5	18			
13/16	.889 .902 .9375 .9449 .9675 .9688 .9842	22.581 22.911 23.812 24.0 24.575 24.606 25.0	(10)		14		26			20	12	16	10					20							12	16	20	28	32	2.5	1.5	1.0		2.5	2.0	1.5	1.0	13/16	14		14				
7/8	1.014 1.0236 1.041 1.046 1.0625 1.063 1.1024	25.755 26.0 26.441 26.568 26.988 27.0 28.0	9	11	14	24	26		9	14	20	12	16	9	14	20	9	14	20							12	16	20	28	32	2.5	1.5	1.0		2.5	2.0	1.5	1.0	7/8	20		16	18		
15/16	1.114 1.125 1.155 1.1811 1.1875	28.3 28.575 29.337 30.0 30.162	(9)		14		26			20	12	16	9					20							12	16	20	28	32	3.0	2.0	1.5	1.0	3.0	2.0	1.5	1.0	15/16	14 parallel		14				
1	1.1024 1.114 1.125 1.155 1.1811 1.1875	28.0 28.3 28.575 29.337 30.0 30.162		8	10	12	24	26	8	14	20	8	12	16	8	14	20	8	12	20			8	12	16	20	28	32		2.0	1.5	1.0		2.0	1.5	1.0	1	20		20					
1 1/16	1.063 1.1024 1.114 1.125 1.155 1.1811 1.1875	27.0 28.0 28.3 28.575 29.337 30.0 30.162								18	12	16	7					18		18									3.0	2.0	1.5	1.0	3.0	2.0	1.5	1.0	1 1/16	14	14		21	16			
1 1/8	1.2598 1.29 1.2992 1.3082 1.309 1.3125	32.0 32.766 33.0 33.228 33.249 33.338	7	9	12		26	16	7	12	18	8	12	16	7	12	18	7	12				8	12	16	20	28		3.5	2.0	1.5	1.0	3.5	3.0	2.0	1.5	1.0	1 1/8	20		14 parallel				
1 3/16	1.37 1.375 1.378 1.405 1.4173 1.4375 1.45	34.798 34.925 35.0 35.687 36.0 36.512 36.83	(6)	8	12		26		6	12	18	8	12	16	6	12	18	6	12			6	8	12	16	20	28			2.0	1.5	1.0		2.0	1.5	1.0	1 3/16	20		29	16				
1 1/2	1.4567 1.492 1.4961 1.5	37.0 37.897 38.0 38.1					24	LH													18	12	16	6								4.0	3.0	2.0	1.5	1.0	4.0	3.0	2.0	1.5	1 1/2	20		29	16
1 5/16	1.492 1.4961 1.5	37.897 38.0 38.1					24	LH													18	12	16	6								3.5	2.0	1.5	1.0	3.5	3.0	2.0	1.5	1 5/16	11	11 1/2	11 taper (copper)		

