


COBALT 3/8" SHANK SILVER & DEMING DRILLS

ICS WIS

HEAVY DUTY

135° SPLIT POINT

ITEM NO.	ILLUSTRATION	CUTTING APPLICATION	STEEL SPECS	TECHNICAL DATA
RSDC	 GOLD COBALT FINISH	For portable or machine drilling in hard steels, stainless steels and other hard materials. The split point is self centering and breaks up chips.	M42	135° Split Point or Notched Point


When ordering, specify 3/8" shank with 1/2" step shank (illustrated above) or 3/8" straight shank.

Fractional Sizes (Reduced Shank) 33/64" to 1" Dia.


SIZE	DEC. EQUIV.	ITEM NO.	PRICE	SIZE	DEC. EQUIV.	ITEM NO.	PRICE	SIZE	DEC. EQUIV.	ITEM NO.	PRICE
33/64	.5156	RSDC033	48.34	11/16	.6875	RSDC044	63.28	55/64	.8594	RSDC055	83.58
17/32	.5312	RSDC034	48.34	45/64	.7031	RSDC045	66.96	7/8	.8750	RSDC056	83.58
35/64	.5469	RSDC035	51.28	23/32	.7188	RSDC046	66.96	57/64	.8906	RSDC057	87.16
9/16	.5625	RSDC036	51.28	47/64	.7344	RSDC047	69.56	29/32	.9062	RSDC058	87.16
37/64	.5781	RSDC037	54.86	3/4	.7500	RSDC048	69.56	59/64	.9219	RSDC059	93.04
19/32	.5938	RSDC038	54.86	49/64	.7656	RSDC049	73.82	15/16	.9375	RSDC060	93.04
39/64	.6094	RSDC039	57.34	25/32	.7812	RSDC050	73.82	61/64	.9531	RSDC061	98.08
5/8	.6250	RSDC040	57.34	51/64	.7969	RSDC051	77.38	31/32	.9688	RSDC062	98.08
41/64	.6460	RSDC041	61.04	13/16	.8125	RSDC052	77.38	63/64	.9844	RSDC063	107.86
21/32	.6562	RSDC042	61.04	53/64	.8281	RSDC053	80.64	1	1.0000	RSDC100	107.86
43/64	.6719	RSDC043	63.28	27/32	.8438	RSDC054	80.64				

HIGH SPEED STEEL and COBALT 3/8" SHANK SILVER & DEMING DRILL SETS

METAL INDEX

DESCRIPTION	TYPE OF DRILL	ITEM NO.	PRICE
8 PC DRILL SET Sizes 9/16 to 1 by 16ths 	General Purpose 3/8 shank S & D Drills - 118° Pt.	DSW-RSD-8	247.46
	Heavy Duty 3/8 shank S & D Drills - 135° Split Pt.	DSW-RSDHB-8	311.16
	Cobalt 3/8 shank S & D Drills - 135° Split Pt.	DSW-RSDC-8	559.60

3/8" SHANK SILVER & DEMING DRILL MERCHANDISER

DESCRIPTION	TYPE OF DRILL	ITEM NO.	PRICE
8 PC DRILL DISPLAY Sizes 9/16 to 1 by 16ths Size: 18 x 12-1/2 	General Purpose - 3/8 shank S & D Drills - 118° Point	DM-RSD-8	252.54