

# CARBIDE TIPPED MASONRY HAMMER DRILLS - SDS-MAX

ICS USA

HEAVY DUTY

HAMMER DRILL POINT

5 SLOT  
SDS-MAX SHANK



PARABOLIC  
FLUTE

SINGLE CUTTER DESIGN

Carbide Tipped SDS-MAX Heavy Duty Slot Drive Masonry Hammer Drills with single cutting edge are designed for use with large SDS-MAX drive rotary hammers. SDS-MAX drive hammer bits have 5 U-shaped slots cut into the .708 diameter shank, 3 positive rotary drive slots, and 2 ball retainer slots to hold bit in rotary hammer. They are used for drilling large diameter holes in concrete, masonry and stone.

NOMINAL		DRILLING DEPTH	ITEM NO.	PRICE
SIZE	LENGTH			
3/8	13-1/2	7	MD-MAX024X13	59.24
1/2	13-1/2	7	MD-MAX032X13	61.52
1/2	21	16	MD-MAX032X21	74.54
1/2	30	25	MD-MAX032X30	CALL
1/2	36	31	MD-MAX032X36	124.66
9/16	13	7	MD-MAX036X13	61.40
9/16	21	16	MD-MAX036X21	85.26
5/8	13	7	MD-MAX040X13	62.64
5/8	21	16	MD-MAX040X21	82.40
5/8	30	25	MD-MAX040X30	82.40
5/8	36	31	MD-MAX040X36	142.62
3/4	13	7	MD-MAX048X13	56.76
3/4	21	16	MD-MAX048X21	73.86
3/4	30	25	MD-MAX048X30	CALL
3/4	36	31	MD-MAX048X36	149.94
7/8	13	8	MD-MAX056X13	68.10
7/8	21	16	MD-MAX056X21	85.00
1	13	8	MD-MAX100X13	77.04
1	21	16	MD-MAX100X21	100.32
1	36	31	MD-MAX100X36	188.16
1-1/8	13	8	MD-MAX108X13	85.74
1-1/8	21	16	MD-MAX108X21	109.04
1-1/4	15	10	MD-MAX116X15	108.74
1-1/4	21	16	MD-MAX116X21	129.88
1-3/8	21	16	MD-MAX124X21	162.64
1-1/2	21	16	MD-MAX132X21	164.48

5 SLOT SHANK (SDS-MAX®) BITS FIT THE FOLLOWING HAMMERS  
(Complete Global Reference on Pages 162-163)

BOSCH®	HILTI®	HILTI®
11216	TE-54	TE 52, 60
SDS-MAX	TE-Y (New)	TE 72, 92

## Quick Reference for 5 Slot Shank (SDS-MAX) Tools

SDS ADAPTERS	A & B TAPER ADAPTERS	HAMMER CORE BITS	HAMMER CHISELS
PAGE NO. OF ITEMS AVAILABLE			
148	155	140-141	160-161