

**CARBIDE TIPPED  
MASONRY (9/16" HEX SHANK) HAMMER DRILLS**

**ICS USA**

**HEAVY DUTY**

**HAMMER DRILL POINT**

**SKIL 728  
HEX SHANK**



**WIDE  
SPIRAL**

Carbide Tipped Heavy Duty 9/16" Hex Shank Masonry Hammer Drills, commonly classified as the Skil 728 Hex Shank, are designed to fit the following 9/16" hex drive rotary hammers:

Skil 628, 728, 731, 731, 732, 1760  
Milwaukee 5325, 5326

Black and Decker 5048  
Miller Falls SP 499K

Rockwell 602, 1602, 606, 616

(Complete Global Reference on Pages 162-163)

9/16" Hex shank rotary hammer drills have 6 flats on the shank to ensure a positive drive action and a flat bottom on the end of the shank for tough hammering of aggregate. They are used for drilling holes from 3/8" to 1-1/2" in concrete, masonry and stone.

NOMINAL		DRILLING DEPTH	ITEM NO.	PRICE
SIZE	LENGTH			
7/16	10	4-1/2	MD-728-028X10	46.58
1/2	10	4-1/2	MD-728-032X10	52.80
9/16	13	7	MD-728-036X13	56.38
5/8	10	4-1/2	MD-728-040X10	58.78
5/8	16	10-1/2	MD-728-040X16	73.42
5/8	22	16-1/2	MD-728-040X22	88.34
11/16	13	7	MD-728-044X13	66.24
7/8	10	4-1/2	MD-728-056X10	69.04
7/8	17	11-1/2	MD-728-056X17	86.94
7/8	22	16-1/2	MD-728-056X22	97.90
1	12	7	MD-728-100X12	79.58

NOMINAL		DRILLING DEPTH	ITEM NO.	PRICE
SIZE	LENGTH			
1	17	11-1/2	MD-728-100X17	92.96
1	22	17	MD-728-100X22	105.98
1-1/8	17	11-1/2	MD-728-108X17	103.58
1-1/8	22	17	MD-728-108X22	120.48
1-1/4	17	11-1/2	MD-728-116X17	126.34
1-1/4	22	17	MD-728-116X22	143.24
1-3/8	17	11-1/2	MD-728-124X17	143.24
1-3/8	22	17	MD-728-124X22	167.62
1-1/2	17	11-1/2	MD-728-132X17	158.70
1-1/2	22	17	MD-728-132X22	187.40


**CARBIDE TIPPED  
MASONRY (3/8" HEX SHANK) HAMMER DRILLS**

**ICS USA**

**HEAVY DUTY**

**HAMMER DRILL POINT**

**SKIL 706  
HEX SHANK**



**WIDE  
SPIRAL**

Carbide Tipped Heavy Duty 3/8" Hex Shank Masonry Hammer Drills, commonly referred to as the Skil 706 hex shank, are designed for the following 3/8" hex drive rotary hammers:

Black and Decker 5040, 5048  
Milwaukee M06

Rockwell 600, 601  
Skil 706, 707, 708, 1706, 511

Ramset 620

3/8" hex shank rotary hammer drills have 6 flats on the shank to ensure a positive drive action and a flat bottom on the end of the shank for tough hammering of aggregate. They are used for drilling holes from 3/8" to 7/8" in concrete, masonry and stone.

NOMINAL		DRILLING DEPTH	ITEM NO.	PRICE
SIZE	LENGTH			
3/8	9	5	MD-706-024X09	
3/8	14	10	MD-706-024X14	
7/16	9	5	MD-706-028X09	
1/2	10	6	MD-706-032X10	
1/2	14	10	MD-706-032X14	
1/2	21	17	MD-706-032X21	
5/8	10	6	MD-706-040X10	
5/8	12	8	MD-706-040X12	

NOMINAL		DRILLING DEPTH	ITEM NO.	PRICE
SIZE	LENGTH			
5/8	16	12	MD-706-040X16	
5/8	21	17	MD-706-040X21	
11/16	10	6	MD-706-044X10	
1/2	10	6	MD-706-048X10	
3/4	16	12	MD-706-048X16	
27/32	10	6	MD-706-054X10	
7/8	10	6	MD-706-056X10	
7/8	16	12	MD-706-056X16	

**DISCONTINUED**