


# HIGH SPEED STEEL BRIDGE REAMERS - HEX SHANK

**ICS WIS**

**HEAVY DUTY**

**RIGHT HAND CUT**

SAFETY STYLE  
HEX SHANK



LEFT HAND  
FLUTE

HELICAL FLUTE

High Speed Steel Hex Shank Bridge Reamers are designed to be used in portable pneumatic equipment for structural steel erection. Their short overall length makes them useful in close quarters. Hex shank sizes are the same as the socket size for the bolt being used in the reamed hole. They are sometimes referred to as Erector Reamers. All ICS Safety Style Hex Shank Reamers are designed to protect against the danger and loss of falling objects such as a reamer. See OSHA 29CFR Part 1926.759 (falling object protection).

SIZE	DEC. EQUIV.	DIAMETER AT POINT	HEX SHANK	NOMINAL LENGTHS		ITEM NO.	PRICE
				FLUTE	OVERALL		
7/16	.4375	17/64	1-1/16	4-3/8	5-7/8	<b>BRHFHX028</b>	51.16
1/2	.5000	5/16	1-1/16	5-1/8	6-5/8	<b>BRHFHX032</b>	53.40
9/16	.5625	3/8	1-1/16	5-1/8	6-5/8	<b>BRHFHX036</b>	55.58
5/8	.6250	25/64	1-1/16	6-1/8	7-5/8	<b>BRHFHX040</b>	64.04
11/16	.6875	13/32	1-1/16	7-1/8	8-5/8	<b>BRHFHX044</b>	76.90
3/4	.7500	15/32	1-1/4	7-3/8	8-7/8	<b>BRHFHX048</b>	84.02
13/16	.8125	35/64	1-1/4	7-3/8	8-7/8	<b>BRHFHX052</b>	88.72
7/8	.8750	39/64	1-7/16	7-3/8	8-7/8	<b>BRHFHX056</b>	100.28
15/16	.9375	43/64	1-7/16	7-3/8	8-7/8	<b>BRHFHX060</b>	108.08
1	1.0000	47/64	1-7/16	7-3/8	8-7/8	<b>BRHFHX100</b>	116.66
1-1/16	1.0625	13/16	1-5/8	7-3/8	8-7/8	<b>BRHFHX104</b>	131.26
1-1/8	1.1250	55/64	1-5/8	7-3/8	8-7/8	<b>BRHFHX108</b>	147.94
1-3/16	1.1875	59/64	1-13/16	7-3/8	8-7/8	<b>BRHFHX112</b>	165.38
1-1/4	1.2500	63/64	1-13/16	7-3/8	11-1/2	<b>BRHFHX116</b>	185.86
1-5/16	1.3125	1-1/16	2	7-3/8	11-1/2	<b>BRHFHX120</b>	190.78
1-3/8	1.3750	1-1/8	2	7-3/8	11-1/2	<b>BRHFHX124</b>	218.92
1-7/16	1.4375	1-3/16	2	7-3/8	11-1/2	<b>BRHFHX128</b>	227.60
1-1/2	1.5000	1-1/4	2	7-3/8	11-1/2	<b>BRHFHX132</b>	258.40
1-9/16	1.5625	1-1/4	2	7-3/8	11-1/2	<b>BRHFHX136</b>	350.92
1-5/8	1.6250	1-1/4	2	7-3/8	11-1/2	<b>BRHFHX140</b>	358.06
1-11/16	1.6875	1-3/8	2	7-3/8	11-1/2	<b>BRHFHX144</b>	368.90
1-3/4	1.7500	1-3/8	2	7-3/8	11-1/2	<b>BRHFHX148</b>	404.76
1-13/16	1.8125	1-7/16	2	7-3/8	11-1/2	<b>BRHFHX152</b>	422.70
1-7/8	1.8750	1-1/2	2	7-3/8	11-1/2	<b>BRHFHX156</b>	440.64
1-15/16	1.9375	1-1/2	2	7-3/8	11-1/2	<b>BRHFHX160</b>	458.62
2	2.0000	1-3/4	2	7-3/8	11-1/2	<b>BRHFHX200</b>	476.58