

HIGH SPEED STEEL


BEARING LOCKNUT HEXAGON RETHREADING DIES

ICS USA

HEAVY DUTY

GROUND THREAD

High Speed Steel Bearing Locknut Hexagon Rethreading Dies are designed for rethreading damaged threads on bearing locknut spindles and to clean out built up locking compound on threads. All dies conform to ABMA (American Bearing Manufacturer's Association) standards.



| ABMA LOCKNUT NO. | THREAD SIZE | DIAMETER ACROSS FLATS | ITEM NO. | PRICE |
|------------------|-------------|-----------------------|----------|----------------|
| #00 | .391 - 32 | 7/8 | BLHTD#00 | - |
| #01 | .469 - 32 | 1-1/16 | BLHTD#01 | - |
| #02 | .586 - 32 | 1-1/4 | BLHTD#02 | - |
| #03 | .664 - 32 | 1-7/16 | BLHTD#03 | - |
| #04 | .781 - 32 | 1-5/8 | BLHTD#04 | - |
| #05 | .969 - 32 | 1-13/16 | BLHTD#05 | CALL FOR PRICE |
| #06 | 1.173 - 18 | 2-3/16 | BLHTD#06 | CALL FOR PRICE |
| #07 | 1.376 - 18 | 2-3/8 | BLHTD#07 | CALL FOR PRICE |
| #08 | 1.563 - 18 | 3-1/8 | BLHTD#08 | - |
| #09 | 1.767 - 18 | 3-1/8 | BLHTD#09 | - |
| #10 | 1.967 - 18 | 3-1/2 | BLHTD#10 | - |
| #11 | 2.157 - 18 | 3-1/2 | BLHTD#11 | - |
| #12 | 2.360 - 18 | 4-1/2 | BLHTD#12 | - |
| #13 | 2.548 - 18 | 4-1/2 | BLHTD#13 | - |

| ABMA LOCKNUT NO. | THREAD SIZE | DIAMETER ACROSS FLATS | ITEM NO. | PRICE |
|------------------|-------------|-----------------------|----------|----------------|
| #14 | 2.751 - 18 | 4-1/2 | BLHTD#14 | - |
| #15 | 2.933 - 12 | 5 | BLHTD#15 | - |
| #16 | 3.137 - 12 | 5 | BLHTD#16 | - |
| #17 | 3.340 - 12 | 5 | BLHTD#17 | - |
| #18 | 3.527 - 12 | 6 | BLHTD#18 | - |
| #19 | 3.730 - 12 | 6 | BLHTD#19 | CALL FOR PRICE |
| #20 | 3.918 - 12 | 6 | BLHTD#20 | CALL FOR PRICE |
| #21 | 4.122 - 12 | 7 | BLHTD#21 | CALL FOR PRICE |
| #22 | 4.325 - 12 | 7 | BLHTD#22 | - |
| #24 | 4.716 - 12 | 7 | BLHTD#24 | - |
| #26 | 5.106 - 12 | 8 | BLHTD#26 | - |
| #28 | 5.497 - 12 | 8 | BLHTD#28 | - |
| #30 | 5.888 - 12 | 8 | BLHTD#30 | - |

CARBON STEEL


BEARING LOCKNUT HEXAGON RETHREADING DIES

ICS USA

GENERAL PURPOSE

CUT THREAD

Carbon Steel Bearing Locknut Hexagon Rethreading Dies are designed for rethreading damaged threads on bearing locknut spindles and to clean out built up locking compound on threads. All dies conform to ABMA (American Bearing Manufacturer's Association) standards.



| ABMA LOCKNUT NO. | THREAD SIZE | DIAMETER ACROSS FLATS | ITEM NO. | PRICE |
|------------------|-------------|-----------------------|----------|----------------|
| #00 | .391 - 32 | 7/8 | BLHRD#00 | - |
| #01 | .469 - 32 | 1-1/16 | BLHRD#01 | - |
| #02 | .586 - 32 | 1-1/4 | BLHRD#02 | - |
| #03 | .664 - 32 | 1-7/16 | BLHRD#03 | - |
| #04 | .781 - 32 | 1-5/8 | BLHRD#04 | - |
| #05 | .969 - 32 | 1-13/16 | BLHRD#05 | CALL FOR PRICE |
| #06 | 1.173 - 18 | 2-3/16 | BLHRD#06 | CALL FOR PRICE |
| #07 | 1.376 - 18 | 2-3/8 | BLHRD#07 | CALL FOR PRICE |
| #08 | 1.563 - 18 | 3-1/8 | BLHRD#08 | - |
| #09 | 1.767 - 18 | 3-1/8 | BLHRD#09 | - |
| #10 | 1.967 - 18 | 3-1/2 | BLHRD#10 | - |
| #11 | 2.157 - 18 | 3-1/2 | BLHRD#11 | - |
| #12 | 2.360 - 18 | 4-1/2 | BLHRD#12 | - |
| #13 | 2.548 - 18 | 4-1/2 | BLHRD#13 | - |

| ABMA LOCKNUT NO. | THREAD SIZE | DIAMETER ACROSS FLATS | ITEM NO. | PRICE |
|------------------|-------------|-----------------------|----------|----------------|
| #14 | 2.751 - 18 | 4-1/2 | BLHRD#14 | - |
| #15 | 2.933 - 12 | 5 | BLHRD#15 | - |
| #16 | 3.137 - 12 | 5 | BLHRD#16 | - |
| #17 | 3.340 - 12 | 5 | BLHRD#17 | - |
| #18 | 3.527 - 12 | 6 | BLHRD#18 | - |
| #19 | 3.730 - 12 | 6 | BLHRD#19 | - |
| #20 | 3.918 - 12 | 6 | BLHRD#20 | CALL FOR PRICE |
| #21 | 4.122 - 12 | 7 | BLHRD#21 | CALL FOR PRICE |
| #22 | 4.325 - 12 | 7 | BLHRD#22 | CALL FOR PRICE |
| #24 | 4.716 - 12 | 7 | BLHRD#24 | - |
| #26 | 5.106 - 12 | 8 | BLHRD#26 | - |
| #28 | 5.497 - 12 | 8 | BLHRD#28 | - |
| #30 | 5.888 - 12 | 8 | BLHRD#30 | - |
| #30 | 5.888 - 12 | 8 | BLHTD#30 | - |