

CARBIDE TIPPED INDUSTRIAL SAW BLADES

335B



STEEL CUTTING BLADES

ICS USA

HEAVY DUTY

TC GRIND

Carbide Tipped Industrial Steel Cutting Blades are designed for dry saw, fine finish cutting on steel, pipe, angle iron, rebar, cast iron, and nail embedded wood. Expansion slots reduce heat build-up and warping. Not designed for high RPM abrasive or wood cutting machines. They cut up to 10 times faster and last up to 30 times longer than abrasive blades.

| DESCRIPTION | DIAMETER | NO. OF TEETH | ARBOR | ITEM NO. | PRICE EACH |
|---|----------|--------------|-------|---------------|------------|
|   | 7-1/4 | 36 | 5/8" | CTCB-SC-0736 | 29.40 |
| | 7-1/4 | 36 | 20mm | CTCB-SC-0736M | 29.40 |
| | 10 | 52 | 5/8" | CTCB-SC-1052 | 38.40 |
| | 12 | 60 | 1" | CTCB-SC-1260 | 51.00 |
| | 14 | 72 | 1" | CTCB-SC-1472 | 67.20 |
| | 14 | 90 | 1" | CTCB-SC-1490 | 70.80 |



ALUMINUM CUTTING BLADES

ICS USA

HEAVY DUTY

TC GRIND

Carbide Tipped Industrial Aluminum Cutting Blades are designed for cutting non-ferrous metals, aluminum, copper, brass and lead. Blades are also used for smooth, chip free cutting of high pressure laminates, plastics, polyurethane, PVC, and acrylics. Expansion slots and heat vents reduce heat build-up and warping. Not designed for cutting steel or ferrous metals.

| DESCRIPTION | DIAMETER | NO. OF TEETH | ARBOR | ITEM NO. | PRICE EACH |
|---|----------|--------------|-----------|---------------|------------|
|   | 7 | 40 | 5/8"-UNIV | CTCB-AL-0740 | CALL |
| | 8 | 64 | 5/8" | CTCB-AL-0864 | 38.40 |
| | 10 | 80 | 5/8" | CTCB-AL-1080 | 50.68 |
| | 10 | 100 | 5/8" | CTCB-AL-10100 | 59.20 |
| | 10 | 120 | 5/8" | CTCB-AL-10120 | 74.76 |
| | 12 | 60 | 1" | CTCB-AL-12060 | 78.12 |
| | 12 | 100 | 1" | CTCB-AL-12100 | 104.16 |
| | 12 | 120 | 1" | CTCB-AL-12120 | 96.18 |



MELAMINE CUTTING BLADES

ICS USA

HEAVY DUTY

TC GRIND

Carbide Tipped Industrial Melamine Blades are designed for chip free cuts in single or double sided melamine, laminates, and veneers. Expansion slots and heat vents reduce heat build-up and warping.

| DESCRIPTION | DIAMETER | NO. OF TEETH | ARBOR | ITEM NO. | PRICE EACH |
|---|----------|--------------|-------|---------------|------------|
|   | 8 | 64 | 5/8" | CTCB-MEL-0864 | 40.32 |
| | 10 | 80 | 5/8" | CTCB-MEL-1080 | 50.82 |
| | 10 | 96 | 5/8" | CTCB-MEL-1096 | 61.74 |
| | 12 | 96 | 1" | CTCB-MEL-1296 | 90.10 |